



Northern Cracking Group (CG)

CELL NO	MIX DESIGNATION	MAX ACG SIZE (mm)	RECYCLED MATERIAL		Air voids at N _{avg}	N _{avg}	MSCR BINDER GRADE	COMMENTS
			ABR %	RAS				
16	SPWBS40L	12.5	30-40	Yes	4.0	80	PG 645-22	
17	SPWBS40L	12.5	20-30		4.0	80	PG 645-22	
18	SPWBS40L	12.5	15-25		4.0	80	PG 645-22	
19	SPWBS30L	12.5	15-25		3.0	100	PG 645-22	
20	SPWBS40A	12.5	25-35		4.0	80	PG 525-34	
21	SPWBS40C	12.5	15-25	No	4.0	80	PG 58H-34	
22	SPWBS40C	12.5	15-25		4.0	80	PG 58H-34	3139 modified for limestone
23	SPWBS40H	12.5	10-20		4.0	80	PG 64E-34	Highly modified asphalt binder



National Center for Asphalt Technology
NCAT
 at AUBURN UNIVERSITY

2018 TEST TRACK CONFERENCE

 MARCH 27-29, 2018
 AUBURN, AL

National Center for Asphalt Technology
NCAT
 at AUBURN UNIVERSITY

Dr. R. Buzz Powell, PE
Assistant Director & Test Track Manager
 277 Technology Parkway
 Auburn, AL 36830
 Phone: (334) 844-6857
 Cell: (334) 750-6293
 Email: buzz@auburn.edu
 Web: www.pavetrack.com
 Twitter: [www.twitter.com/pavetrack](https://twitter.com/pavetrack)